CPWplus Weighing Scales

Speed, Performance, Value - Perfect Balance

- 4 Weighing units (kg, lb:oz, lb, oz)
- Simple 4 button operation
- Hold function
- Full range tare
- Zero Tracking
- Large backlit LCD display
- Wall mount bracket
- Large stainless steel pan
- Modern low profile design
- Splashproof to protect from accidental spills
- Precision load cell technology
- Colour coded, sealed keypad
- RS-232 bi-directional interface
- Low battery indication
- Auto sleep / power down function to save battery life
- Battery power (6 x AA Batteries)
- AC Adapter
- Weighing
- Animal / dynamic weighing



www.adamequipment.com

Technical Specifications

Model	CPWplus 6	CPWplus 15	CPWplus 35	CPWplus 75	CPWplus 150	CPWplus 200
Maximum capacity	13lb/6000g	33lb/15kg	75lb/35kg	165lb/75kg	330lb/150kg	440lb/200kg
Readability	0.005lb/2g	0.01lb/5g	0.02lb/10g	0.05lb/20g	0.1lb/50g	0.1lb/50g
Tare range	Full	Full	Full	Full	Full	Full
Repeatability (S.D.)	2g	5g	10g	20g	50g	50g
Linearity (±)	4g	10g	20g	40g	100g	100g
Platform size	11.8ï¿½11.8" / 300ï¿½300mm					

The same models are available with additional display on a Pillar as series denoted with 'P'.

General Specifications

Units of measurement	Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz)
Typical stabilisation time	2 Sec
Interface	RS-232 bi-directional Interface
Calibration	Automatic External with user selectable calibration mass
Display	LCD with minimum 22mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together
Power supply	6 AA size non-rechargeable batteries in a compartment located in the base or 12VAC 150mA from external adapter
Operating temperature	32°F - 104°F
Housing	Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform
Overall dimensions (wxdxh)	11.8ï¿½11.8ï¿½2" / 300ï¿½300ï¿½50mm
Dimensions notes	Indicator: 220 x 95 x 43mm (w x d x h)

Key Accessories

· Hard Carry Case with Lock
· AdamDU - Data Collection Program
· RS-232 to PC Cable
· RS-232 to USB Interface Cable (must be ordered with 30740102
· ATP Thermal Printer
· Thermal Paper For Adam ATP (10 pack)

Adam Equipment - offices worldwide

www.adamequipment.com

Adam Equipment follows a policy of continuous improvement and reserves the right to change specifications without notice. © May 26th 2013