

## Technical Specifications


Model	CPWplus 35M	CPWplus 75M	CPWplus 150M	CPWplus 200M
Maximum capacity	35kg	75kg	150kg	200kg
Readability	10g	20g	50g	50g
Tare range	Full	Full	Full	Full
Repeatability (S.D.)	10g	20g	50g	50g
Linearity ( $\pm$ )	20g	40g	100g	100g
Platform size	500x500mm			

## General Specifications

Units of measurement	Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz)
Typical stabilisation time	2-3 Sec
Interface	RS-232 bi-directional Interface
Calibration	Automatic External with user selectable calibration mass
Display	LCD with minimum 22mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together
Operating temperature	0° - 40°C
Housing	Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform
Overall dimensions (wxdxh)	500x500x40mm
Dimensions notes	Indicator: 220 x 95 x 43mm (w x d x h)
Net weight	8,9kg

## Key Accessories

- Adam Printer
- Thermal Paper Roll for Adam Printer
- AdamDU - Data Collection Program
- RS-232 to USB Interface Cable (must be ordered with 3074010266 RS232 cable)
- RS-232 to PC Cable
- ATP Thermal Printer
- Thermal Paper for ATP



Adam Equipment - offices worldwide

[www.adamequipment.com](http://www.adamequipment.com)