



Speed, Performance, Value - The Right Balance

- Stainless steel weighing pan with remote indicator
- Large backlit LCD display
- Simple 4 button operation
- Portable with battery power
- Kg/ lb/ oz/ lb & oz switchable
- Tare function
- Mains adapter and wall mounting kit supplied as standard
- Hold function
- RS-232 bi-directional interface
- Mains adapter supplied as standard / battery operation
- Weighing
- Animal / dynamic weighing



Technical Specifications

Model	CPWplus 35	CPWplus 75	CPWplus 150	CPWplus 200
Maximum capacity	35kg	75kg	150kg	200kg
Readability	10g	20g	50g	50g
Tare range	Full	Full	Full	Full
Repeatability (S.D.)	10g	20g	50g	50g
Linearity (\pm)	20g	40g	100g	100g
Platform size	300x300mm			

General Specifications

Units of measurement	Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz)
Typical stabilisation time	2 Sec
Interface	RS-232 bi-directional Interface
Calibration	Automatic External with user selectable calibration mass
Display	LCD with minimum 25mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together
Power supply	6 AA size non-rechargeable batteries in a compartment located in the base or 12VAC 150mA from external adapter
Operating temperature	0° - 40°C
Housing	Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform
Overall dimensions (wxdxh)	300x300x50mm
Dimensions notes	Indicator: 220 x 95 x 43mm (w x d x h)
Net weight	4kg

Key Accessories

- Hard Carry Case with Lock
- Adam Printer
- Thermal Paper Roll for Adam Printer
- AdamDU - Data Collection Program
- RS-232 Cable



Adam Equipment - offices worldwide

www.adamequipment.com