



Speed, Performance, Value - The Right Balance

- 5 weighing units (kg, g, lb, oz, lbs:oz)
- Adjustable filters
- Memory accumulation
- Easy to use keypad
- Date and time
- Full range tare
- Tare function
- Pre-set weighing with alarm
- Check-weighing with low and high limits
- Check weighing LED bar graph
- Large backlit LCD display
- Capacity tracker
- Non-slip adjustable levelling feet
- Overload protection
- Large stainless steel pan
- Colour coded, sealed keypad
- Full colour coded keypad with numeric entry
- Simple user-friendly operation
- Splashproof to protect from accidental spills
- Precision load cell technology
- Internal counting resolution 1:400,000
- Easy access to the rechargeable battery
- RS-232 bi-directional interface
- External calibration
- Rechargeable battery up to 90 hours operation
- Auto sleep / power down function to save battery life
- Zero adjust facility to enable zero reading
- Low battery indication
- AC Adapter
- Weighing
- Check weighing
- Percentage weighing
- Weight accumulation
- Parts counting



Technical Specifications

Model	CBK 4	CBK 8H	CBK 8	CBK 16	CBK 32	CBK 48
Maximum capacity	4000g	8000g	8000g	16kg	32kg	48kg
Readability	0.1g	0.1g	0.2g	0.5g	1g	2g
Repeatability (S.D.)	0.1g	0.1g	0.2g	0.5g	1g	2g
Linearity (±)	0.2g	0.2g	0.4g	1g	2g	4g
Platform	225x275mm					

General Specifications

Units of measurement	Gram (g), Kilogram (kg)
Interface	RS-232 bi-directional Interface
Calibration	Automatic external
Display	6 digits LCD displays
Battery	Internal Rechargeable battery up to 90 hours
Power supply	230VAC 50/60Hz 120VAC available
Operating temperature	-10°C 40°C
Real-time clock	Real-time clock
Housing	ABS Plastic
Overall dimensions (wxdxh)	315x355x110mm
Net weight	4.1kg

Key Accessories

- Adam Printer
- Thermal Paper Roll for Adam Printer
- In-use Cover
- In-Use Cover pack of 10
- Weigh Below Hanger (factory fitted)
- RS-232 Cable
- AdamDU - Data Collection Program
- Hard Carry Case with Lock
- In-Use Cover pack of 5



Adam Equipment - offices worldwide

www.adamequipment.com