

## Technical Specifications

Model	AQT 200	AQT 250	AQT 600	AQT 1500	AQT 2600	AQT 2000	AQT 5000
Maximum capacity	200g	250g	600g	1500g	2600g	2000g	5000g
Readability	0.01g	0.1g	0.1g	0.1g	0.1g	1g	1g
Resolution	1:20000	1:2500	1:6000	1:15000	1:26000	1:2000	1:5000
Repeatability (S.D.)	0.02g	0.1g	0.1g	0.2g	0.2g	1g	1g
Linearity (±)	0.02g	0.1g	0.1g	0.2g	0.2g	1g	1g
Pan size	130mm Ø						
Units of measurement	Gram (g), Carat (ct), Ounce (Oz), Pennyweight (dWt), Taels Hk. (TL.H), Taels S. (TL.S), Taels T. (TL.T)	Gram (g), Carat (ct), Ounce (Oz), Pennyweight (dWt)	Gram (g), Kilogram (kg), Pound (lb), Ounce (Oz)				
Typical stabilisation time	3 Sec	2 Sec	3 Sec	2 Sec			

## General Specifications

Calibration	Push button using external mass
Display	6 digit LCD, 15mm digits with backlight
Power supply	12VAC @ 150mA adapter or 6 x AA batteries
Operating temperature	0°C - 40°C
Other features	Low battery, stable and zero indicators
Housing	ABS plastic
Draught shield dimensions	180 x 158 x 82mm
Overall dimensions (wxdxh)	195x240x70mm
Net weight	1.2kg

## Key Accessories

- In-use Cover
- Hard Carry Case with Lock



Adam Equipment - offices worldwide

[www.adamequipment.com](http://www.adamequipment.com)