

Technical Specifications

Model	CBD 4	CBD 8	CBD 16	CBD 32	CBD 48
Maximum capacity	4000g	8000g	16kg	32kg	48kg
Readability	0.1g	0.2g	0.5g	1g	2g
Repeatability (S.D.)	0.1g	0.2g	0.5g	1g	2g
Linearity (\pm)	0.2g	0.4g	1g	2g	4g
Pan size	225x275mm				

General Specifications

Internal counting resolution	1:600,000
Tare functions	Full
Functions	Weighing, Parts Counting, Memory Accumulation Function, Preset Weight and Count with Alarm, up to 100 PLUs with description, unit & tare weight
Typical stabilisation time	2 Sec
Interface	Bi-directional RS-232 interface
Calibration	Automatic External
Display	3 x 6 digits LCD digital display
Power supply	Mains power cord/internal rechargeable battery
Operating temperature	0°C - 40°C
Other features	Accuracy enhancement for parts counting, internal rechargeable battery (up to 70 hours of operation)
Housing	ABS plastic, stainless steel platform
Overall dimensions (wxdxh)	315x355x110mm
Net weight	4.4kg

Key Accessories

- Adam Printer
- In-Use Cover pack of 10
- In-use Cover
- Range of Platforms for Remote Scale
- In-Use Cover pack of 5
- Thermal Paper Roll for Adam Printer
- RS-232 Cable
- RS-232 to USB Interface Cable (must be ordered with 3074010266 RS232 cable)
- AdamDU - Data Collection Program
- Hard Carry Case with Lock
- ATP Thermal Printer
- Thermal Paper for ATP



Adam Equipment - offices worldwide

www.adamequipment.com