

Technical Specifications

Model	CPWplus 35L	CPWplus 75L	CPWplus 150L	CPWplus 200L	CPWplus 300L
Maximum capacity	35kg	75kg	150kg	200kg	300kg
Readability	10g	20g	50g	50g	100g
Tare range	Full	Full	Full	Full	Full
Repeatability (S.D.)	10g	20g	50g	50g	100g
Linearity (±)	20g	40g	100g	100g	200g
Platform size	900x600mm				

General Specifications

Units of measurement	Kilogram (kg), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz)
Typical stabilisation time	2-3 Sec
Interface	RS-232 bi-directional Interface
Calibration	Automatic External with user selectable calibration mass
Display	LCD with minimum 25mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together
Operating temperature	0° 40°C
Housing	Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform
Overall dimensions (wxdxh)	900x600x80mm
Dimensions notes	Indicator: 220 x 95 x 43mm (w x d x h)
Net weight	17kg

Key Accessories

- Adam Printer
- Thermal Paper Roll for Adam Printer
- RS-232 Cable
- AdamDU - Data Collection Program
- Rubber non-slip mat for CPWplus L



Adam Equipment - offices worldwide

www.adamequipment.com